

The quietest, most productive indoor/outdoor sweeper available.

Engineered for reliable, industrial-strength sweeping, the Tennant S30 rider sweeper improves indoor and outdoor performance, significantly reduces sound levels and features the exclusive SweepSmart dust control system.

Significantly improve air quality

Create cleaner air while delivering better sweeping results with the SweepSmart dust control system. This 3-stage system filters sub-micron dust particles to a MERV 13 rating on the ASHRAE 20 point scale, resulting in near HEPA levels.

Unrivaled sweeping performance

Easily pick-up everything from fine grains of sand to light debris on almost any terrain or floor surface. The Tennant S30 offers true indoor/outdoor flexibility while delivering exceptional cleaning results.

Unparalleled safety

Focusing on safety, the Tennant S30 provides better operator sightlines, reduced noise levels, and easy operation. This is achieved with a cab forward design, key material and system improvements.



Reliably provide a clean, safe, and productive environment with SweepSmart

Improving air flow filtration and dust control for sweeping, the patent-pending S30 SweepSmart system uses a 3-stage dust control system for unrivaled performance:



STAGE 1

Keep bulky debris, moisture and dirt in the hopper with the *first stage Perma-Filter*.

STAGE 2

Remove fine dust and moisture by redirecting it into the hopper with the *second stage cyclonic filters*.

STAGE 3

Filter sub-micron dust particulates down to 0.5 microns at 99% efficiency with a *third stage, flame retardant, nanofiber canister filter*.

PRODUCTIVE. CLEAN. SAFE.



Reduce downtime, service time, and maintenance costs by quickly accessing the heart of the S30 with EasyOpen service access.




Engineered, fiber-reinforced composite covers are light weight, corrosion resistant, and manufactured with a high-density material. The superior finish makes these covers easy to clean and restorable even if damaged.



Enhance operator safety and productivity with a cab forward ErgoSpace operator compartment.

INSIDE THE S30



A

Ensure operator safety, by alerting and shutting down sweeping functions, if increases in hopper temperature are sensed by Thermo-Sentry.

B

Provide air flow filtration and dry dust control for sweeping all floor surfaces with the SweepSmart system.

C

Effectively remove different types of debris with the II-Speed sweep system. This increases the speed of the main brush, side brush, and vacuum fan by 20%.

D

Improve sweeping results with the retractable, spring loaded flap that re-circulates any debris that may escape over the main brush.

E

Depend on long-term structural reliability with a heavy-gauge steel machine frame designed for greater strength, rigidity, and long life.

KEY AVAILABLE FEATURES



Achieve outstanding results in the harshest environments with dual side brushes which, combined with a large 395 L Duramer hopper, allow you to sweep up to 2030 mm in a single pass.



Minimize risk of damage to both the machine frame and the facility with rounded rear corners and rear tower bumpers that improve turn off from structures (walls and racking), while protecting from accidental contact.



Increase safety and effective operation, in even the most severe environments, with an optional FOPS certified (ISO 3449) pressurized cabin available with heat and air conditioning.



S30 Rider Sweeper

	RESULT	FEATURE
Increased Safety	Improves visibility and response time to obstacles	Cab forward ErgoSpace operator compartment
	Reduces the risk of accidental hopper fires	Thermo-Sentry hopper sensor
	Reduces fatigue and environment noise levels	Lowest noise level for an engine-powered sweeper in this class at 80 dBA
Reduced Costs	Quick, easy maintenance, allows maximum uptime	EasyOpen service access and on-board diagnostics
	Reduces hydraulic temperatures and increases component life	Large-capacity hydraulic oil tank, triple accessory pumps, and micro component in-line filter to provide consistent hydraulic flow and pressure
	Reduces unnecessary downtime and wheel maintenance	Soft ride, solid tires have a significantly higher load capacity, remarkable durability and low maintenance
	Reduces maintenance costs and increases effective cleaning performance	Large spline drive that transfers power deep into the brush core, integrated string and twine guard, and Tennant's patented color coded brush wear indicator
Maximum Productivity	Maximizes dust control while sweeping	SweepSmart 3-stage dust control system provides improved air flow filtration and dust control
	More effectively sweep different types of debris by increasing the main brush, side brush, and vacuum fan speeds up to 20%.	II-Speed Sweeping
	Decreases operator training time and simplifies machine operation	Touch-N-Go operation with simple 1-STEP sweeping begins all operations, remembering previous settings
	Improves handling and patrol sweeping capability	Dynamic steering responsiveness, rear suspension system, and 4-wheel stability for spot cleaning with the S30 X4 model



GENUINE TENNANT PARTS, SUPPLIES & SERVICE

Genuine Tennant Parts Advantage
Operate your machine with confidence by choosing genuine Tennant parts. Only authentic Tennant parts are engineered in conjunction with Tennant equipment. For years of worry-free operation, accept only genuine parts and supplies.

Industry's Only Factory-Direct Service Network
Providing world-class response, completion times and on-site machine service, our factory-trained network is dedicated to keeping your cleaning program up and running.

S30 RIDER SWEEPER

Sweeping System	
Cleaning path	
Single side brush	1,590 mm
Dual side brush	2,030 mm
Main brush	
Main brush length (tubular)	1,145 mm
Main brush lift	Mechanical or Hydraulic
Main brush change	No-tool
Side broom	
Side broom diameter	660 mm
Debris hopper	
Volume capacity	395 L
Weight capacity (plastic)	490 kg
Weight capacity (steel)	545 kg
Dump height (variable to)	1,525 mm
Dump reach	760 mm
Dust Control System	
Filter system (triple stage)	
Stage 1	Perma-Filter
Stage 2	Cyclonic pre-filter
Stage 3	Nanofiber canister filter
Filter area	7,5 m ²
Dust filtration (up to)	0.5 microns @ 99% efficiency
Vacuum fan speed	
Normal sweeping mode	4600 rpm
Litter sweeping mode	5500 rpm
Vacuum diameter	280 mm
Propelling System	
Propel speed forward (variable to)	16/24 km/h
Propel speed reverse (variable to)	5 km/h
Engine-gasoline/LPG	41 kW GM
Engine-diesel	28 kW Kubota
Gradeability	
Full hopper	10 deg/18%
Empty hopper	14 deg/25%
Ground clearance	100 mm
Machine Dimensions	
Length	2,360 mm
Width	1,590 mm
Height	
With overhead guard	2,095 mm
Without overhead guard	1,475 mm
Weight (net)	1,595 kg
Minimum aisle turn	2,870 mm
Sound level	80 dBA

Mid-sized Rider Sweeper

- Deliver unrivaled sweeping performance and dry dust control with 3-stage SweepSmart system
- Clean indoors and out, without compromising performance
- Improve operator safety with low 80 dBA noise rating and innovative cab forward design

S30



SEEING IS BELIEVING
For a demonstration or additional information, send an email to info@tennantco.com.

TENNANT EUROPE NV
Plantin & Moretuslei 220
2018 Antwerp
BELGIUM
Tel: +32 3 217 94 11
Fax: +32 3 217 94 19
E-mail: info@tennant.be
www.tennant.be

TENNANT UK LTD.
Gladstone Road
Northampton NN5 7FX
UNITED KINGDOM
Tel: 00800-2255 8366
Fax: 00800-3298 3662
Tel: 01604 583191 (local rate UK only)
Fax: 01604 587909 (local rate UK only)
E-mail: europa@tennantco.com

TENNANT CEE GmbH
Sommerfeld 1
5202 Neumarkt am Wallersee
AUSTRIA
Tel: +43 (0)6216 4524 & 4525
Fax: +43 (0)6216 4524 20
E-mail: office@tennant-cee.com