

T581 Micro-Rider Scrubber-Dryer

Maneuverability in a Compact Rider

Quiet sound level, intuitive controls and compact design allow for easy operation and anytime cleaning. The T581 is ideal for cleaning large spaces in areas such as retail stores, hospitals and schools.

Available Technologies



**Chem-Dose
Cleaning System**



Maneuverable and Productive

Compact design easily fits into most congested spaces, and can quickly reach many areas of a facility to get more cleaning done.



Simple Operation

Ease of start-up and quick training with one-button cleaning operation that lowers the scrub head and squeegee at the same time.



Versatile Cleaning with Chem-Dose System

Increase consistent cleaning performance and reduce cost to clean with integrated chemical dosing system.

Inside the T581

- 1. Easily change water flow rate** and other cleaning functions from intuitive control panel.
- 2. Multi-stage vacuum motor** for strong water pick-up.
- 3. Quick, mess-free tank draining** with large, pinch-style recovery tank drain hose.
- 4. Large solution tank** with level gauge and drain hose.
- 5. Consistent water pick-up** with durable "V" shaped squeegee design and standard Linatex® squeegee blades.
- 6. Simple no-tools, no-touch brush change system.**



T581 Specifications

FEATURE	SPECIFICATION	
	SELF-PROPEL	SELF-PROPEL
Cleaning path	550 mm	700 mm
Productivity (per hour) theoretical max	3,300 m ² /hr	4,270 m ² /hr
Estimated coverage (per hour)*	2,038 m ² /hr	2,645 m ² /hr
Scrubbing speed	6.0 kmh	
Scrub head and squeegee raise/lower	independent actuators	
Brush/pad speed	150 rpm	220 rpm
Brush/pad pressure	22 kg	10 up to 50 kg
Solution tank capacity	78.5 L	
Recovery tank capacity	80 L	
Battery run time - up-to hours**	2.3	4.5
Battery voltage	24V (2 x 12)	24V (4 x 6)
Dimensions (LxWxH)	1,310 x 673 x 1,030 mm	1,310 x 760 x 1,030 mm
Squeegee width	710 mm	924 mm
Weight (with heaviest battery)	211 kg	283 kg
External radius (wall to wall)	1851 mm	
Maximum climbing angle	8%	16%
Sound level (operator's ear)***	65 dB	
Chem-Dose tank capacity	3 L	

Specifications subject to change without notice.
 *Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.
 **Run times are based on Continuous Scrubbing Run Times.
 ***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information,
 call **+32 3 217 94 11** or email **europe@tennantco.com**

TENNANT EUROPE NV
 tennant.eu